

An praktisch allen bearbeitbaren Materialien einsetzbar.  
**HSS-Bi-Metall Co8 Lochsägen**



Art.-Nr.	Maße	ø Zoll	Drehzahl Aluminiumlegierung/unlegierter Baustahl	Drehzahl Thermoplaste/legierte Stähle
7003470014	ø 14 mm	9/16	690	460
7003470016	ø 16 mm	5/8	600	400
7003470017	ø 17 mm	11/16	570	380
7003470019	ø 19 mm	3/4	510	340
7003470020	ø 20 mm	25/32	460	310
7003470021	ø 21 mm	13/16	460	310
7003470022	ø 22 mm	7/8	440	300
7003470024	ø 24 mm	15/16	400	270
7003470025	ø 25 mm	1	390	260
7003470027	ø 27 mm	1 1/16	360	240
7003470029	ø 29 mm	1 1/8	330	220
7003470030	ø 30 mm	1 3/16	320	220
7003470032	ø 32 mm	1 1/4	300	200
7003470033	ø 33 mm	1 5/16	290	200
7003470035	ø 35 mm	1 3/8	280	200
7003470037	ø 37 mm	1 7/16	260	180
7003470038	ø 38 mm	1 1/2	260	170
7003470040	ø 40 mm	1 9/16	240	160
7003470041	ø 41 mm	1 5/8	240	160
7003470043	ø 43 mm	1 11/16	230	150
7003470044	ø 44 mm	1 3/4	220	150
7003470046	ø 46 mm	1 3/4	210	140
7003470048	ø 48 mm	1 7/8	200	140
7003470051	ø 51 mm	2	190	130
7003470052	ø 52 mm	2 1/16	190	130
7003470054	ø 54 mm	2 1/8	180	120
7003470057	ø 57 mm	2 1/4	170	120
7003470059	ø 59 mm	2 5/16	170	110
7003470060	ø 60 mm	2 3/8	160	110



Art.-Nr.	Maße	Ø Zoll	Drehzahl Aluminiumlegierung/unlegierter Baustahl	Drehzahl Thermoplaste/legierte Stähle
7003470064	Ø 64 mm	2 1/2	150	100
7003470065	Ø 65 mm	2 9/16	150	100
7003470067	Ø 67 mm	2 5/8	150	100
7003470068	Ø 68 mm	2 22/32	150	100
7003470070	Ø 70 mm	2 3/4	140	100
7003470073	Ø 73 mm	2 7/8	140	90
7003470076	Ø 76 mm	3	130	90
7003470079	Ø 79 mm	3 1/8	130	90
7003470083	Ø 83 mm	3 1/4	120	80
7003470086	Ø 86 mm	3 3/8	120	80
7003470089	Ø 89 mm	3 1/2	110	80
7003470092	Ø 92 mm	3 5/8	110	70
7003470095	Ø 95 mm	3 3/4	110	70
7003470098	Ø 98 mm	3 7/8	100	70
7003470102	Ø 102 mm	4	100	70
7003470105	Ø 105 mm	4 1/8	100	70
7003470108	Ø 108 mm	4 1/4	90	60
7003470111	Ø 111 mm	4 3/8	90	60
7003470114	Ø 114 mm	4 1/2	90	60
7003470121	Ø 121 mm	4 3/4	80	60
7003470127	Ø 127 mm	5	80	50
7003470140	Ø 140 mm	5 1/2	70	50
7003470146	Ø 146 mm	5 3/16	70	50
7003470152	Ø 152 mm	6	70	50